


Engineering data (WIN 1109)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.02 ms
Rated voltage	334 V AC (rms)	Thermal time constant	80 min
Rated power	5.5 kW	Rotor inertia	49.5 kgcm ²
Rated speed	2000 rpm	Protection	IP64
Rated torque	26.10 Nm	Color	RAL 9005
Rated current	11.72 A (rms)	Cooling	Convection
Peak torque	85 Nm	Motor-only mass	9.2 kg
Peak current	40.8 A (rms)	Max. axial force 20kh	264 N
Stall torque	30 Nm	Max. radial force 20kh	1390 N*
Stall current	11.6 A (rms)	Max. axial force 100kh	154 N
No load speed	2420 rpm	Max. radial force 100kh	813 N*
EMF constant ±10%	157 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	2.6 Nm / A (rms)		
Torque constant ±10% @ rated load	2.2 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EDS35 (HDSL) single-turn, 24 bits	
Number of poles	10		
Electrical time constant	15.88 ms		
Winding terminal resistance	0.8 Ω		
Rotary field terminal inductance	12.7 mH		
Customs info			
HS Code	85015220		



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

