

Engineering data (WIN 879)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	311 V AC (rms)
Rated power	6.9 kW
Rated speed	2000 rpm
Rated torque	32.80 Nm
Rated current	15.38 A (rms)
Peak torque	120 Nm
Peak current	59.1 A (rms)
Stall torque	40 Nm
Stall current	16.7 A (rms)
No load speed	2620 rpm
EMF constant ±10%	145 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	2.4 Nm / A (rms)
Torque constant ±10% @ rated load	2.1 Nm / A (rms)
Number of poles	10
Electrical time constant	18.14 ms
Winding terminal resistance	0.43 Ω
Rotary field terminal inductance	7.8 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	6000 rpm
Mech. time constant	0.89 ms
Thermal time constant	90 min
Rotor inertia	69 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	20.2 kg
Max. axial force 20kh	281 N
Max. radial force 20kh	1478 N*
Max. axial force 100kh	164 N
Max. radial force 100kh	864 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

