


Engineering data (WIN 860)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.75 ms
Rated voltage	265 V AC (rms)	Thermal time constant	100 min
Rated power	9.4 kW	Rotor inertia	88 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	30.00 Nm	Color	RAL 9005
Rated current	24.35 A (rms)	Cooling	Convection
Peak torque	150 Nm	Motor-only mass	24 kg
Peak current	109.3 A (rms)	Max. axial force 20kh	256 N
Stall torque	50 Nm	Max. radial force 20kh	1346 N*
Stall current	31.5 A (rms)	Max. axial force 100kh	150 N
No load speed	3950 rpm	Max. radial force 100kh	787 N*
EMF constant ±10%	98 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.59 Nm / A (rms)		
Torque constant ±10% @ rated load	1.23 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EDM35 (HDSL) multi-turn, 20+12 bits	
Number of poles	10		
Electrical time constant	20.00 ms		
Winding terminal resistance	0.13 Ω		
Rotary field terminal inductance	2.6 mH		
Customs info			
HS Code	85015230		


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

