


Engineering data (WIN 1154)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.79 ms
Rated voltage	269 V AC (rms)	Thermal time constant	100 min
Rated power	8.5 kW	Rotor inertia	88 kgcm ²
Rated speed	2000 rpm	Protection	IP64
Rated torque	40.40 Nm	Color	RAL 9005
Rated current	21.82 A (rms)	Cooling	Convection
Peak torque	150 Nm	Motor-only mass	23.2 kg
Peak current	78.9 A (rms)	Max. axial force 20kh	308 N
Stall torque	50 Nm	Max. radial force 20kh	1622 N*
Stall current	22.7 A (rms)	Max. axial force 100kh	180 N
No load speed	2850 rpm	Max. radial force 100kh	949 N*
EMF constant ±10%	133 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	2.2 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	1.9 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EDM35 (HDSL) multi-turn, 20+12 bits
Electrical time constant	19.60 ms	Brake	
Winding terminal resistance	0.25 Ω	Braking torque	36.00 Nm
Rotary field terminal inductance	4.9 mH	Voltage	24 V DC
Customs info		Power @20°C	26.0 W
HS Code	85015230	Current @20°C	1.08 A
		Inertia	6.20 kgcm ²
		Mass	2.85 kg


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

