

Engineering data (WIN 1343)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	199 V AC (rms)
Rated power	327 W
Rated speed	6000 rpm
Rated torque	0.52 Nm
Rated current	1.19 A (rms)
Peak torque	2.47 Nm
Peak current	5.9 A (rms)
Stall torque	0.75 Nm
Stall current	1.44 A (rms)
No load speed	12000 rpm
EMF constant ±10%	31.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.521 Nm / A (rms)
Torque constant ±10% @ rated load	0.437 Nm / A (rms)
Number of poles	10
Electrical time constant	1.13 ms
Winding terminal resistance	12.438 Ω
Rotary field terminal inductance	14.1 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	2.62 ms
Thermal time constant	20 min
Rotor inertia	0.33 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.3 kg
Max. axial force 20kh	37 N
Max. radial force 20kh	195 N*
Max. axial force 100kh	22 N
Max. radial force 100kh	114 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDS35 (HDSL) single-turn, 24 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

