


Engineering data (WIN 1270)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.53 ms
Rated voltage	276 V AC (rms)	Thermal time constant	24 min
Rated power	490 W	Rotor inertia	0.5 kgcm²
Rated speed	6000 rpm	Protection	IP64
Rated torque	0.78 Nm	Color	RAL 9005
Rated current	1.27 A (rms)	Cooling	Convection
Peak torque	4.94 Nm	Motor-only mass	1.6 kg
Peak current	8.33 A (rms)	Max. axial force 20kh	43 N
Stall torque	1.3 Nm	Max. radial force 20kh	225 N*
Stall current	1.77 A (rms)	Max. axial force 100kh	25 N
No load speed	8140 rpm	Max. radial force 100kh	131 N*
EMF constant ±10%	44.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.734 Nm / A (rms)		
Torque constant ±10% @ rated load	0.614 Nm / A (rms)	Sensors	
Number of poles	10	Temperature	PT1000 {PT1000}
Electrical time constant	1.44 ms	Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits
Winding terminal resistance	9.598 Ω		
Rotary field terminal inductance	13.8 mH		
Customs info			
HS Code	85015100		



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

