


Engineering data (WIN 1621)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	1.38 ms
Rated voltage	167 V AC (rms)	Thermal time constant	28 min
Rated power	539 W	Rotor inertia	0.68 kgcm²
Rated speed	5000 rpm	Protection	IP64
Rated torque	1.03 Nm	Color	RAL 9005
Rated current	2.24 A (rms)	Cooling	Convection
Peak torque	6.65 Nm	Motor-only mass	1.9 kg
Peak current	14 A (rms)	Max. axial force 20kh	52 N
Stall torque	1.75 Nm	Max. radial force 20kh	276 N*
Stall current	3.16 A (rms)	Max. axial force 100kh	31 N
No load speed	6540 rpm	Max. radial force 100kh	161 N*
EMF constant ±10%	33.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.554 Nm / A (rms)		
Torque constant ±10% @ rated load	0.460 Nm / A (rms)	Sensors	
Number of poles	10	Temperature	PT1000 {PT1000}
Electrical time constant	1.43 ms	Feedback	EKS36 (HDSL) single-turn, 17 bits
Winding terminal resistance	3.607 Ω		
Rotary field terminal inductance	5.17 mH		

Customs info	
HS Code	85015100


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

