


Engineering data (WIN 1530)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	2.62 ms
Rated voltage	171 V AC (rms)	Thermal time constant	20 min
Rated power	298 W	Rotor inertia	0.33 kgcm ²
Rated speed	5000 rpm	Protection	IP64
Rated torque	0.57 Nm	Color	RAL 9005
Rated current	1.29 A (rms)	Cooling	Convection
Peak torque	2.47 Nm	Motor-only mass	1.3 kg
Peak current	5.9 A (rms)	Max. axial force 20kh	42 N
Stall torque	0.75 Nm	Max. radial force 20kh	219 N*
Stall current	1.44 A (rms)	Max. axial force 100kh	24 N
No load speed	6930 rpm	Max. radial force 100kh	128 N*
EMF constant ±10%	31.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.521 Nm / A (rms)		
Torque constant ±10% @ rated load	0.442 Nm / A (rms)		
Number of poles	10	Sensors	
Electrical time constant	1.13 ms	Temperature	PT1000 {PT1000}
Winding terminal resistance	12.438 Ω	Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2
Rotary field terminal inductance	14.1 mH	Brake	
Customs info		Braking torque	4.50 Nm
HS Code	85015100	Voltage	24 V DC
		Power @20°C	12.0 W
		Current @20°C	0.50 A
		Inertia	0.20 kgcm ²
		Mass	0.47 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

