

Engineering data (WIN 1579)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	177 V AC (rms)
Rated power	471 W
Rated speed	6000 rpm
Rated torque	0.75 Nm
Rated current	1.9 A (rms)
Peak torque	8.36 Nm
Peak current	18.8 A (rms)
Stall torque	2.2 Nm
Stall current	4.29 A (rms)
No load speed	7070 rpm
EMF constant ±10%	31 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.513 Nm / A (rms)
Torque constant ±10% @ rated load	0.395 Nm / A (rms)
Number of poles	10
Electrical time constant	1.58 ms
Winding terminal resistance	2.151 Ω
Rotary field terminal inductance	3.39 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.20 ms
Thermal time constant	32 min
Rotor inertia	0.85 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	2.2 kg
Max. axial force 20kh	49 N
Max. radial force 20kh	260 N*
Max. axial force 100kh	29 N
Max. radial force 100kh	152 N*


** Defined for point of action at ½ output shaft length*

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

