


Engineering data (WIN 1532)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.08 ms
Rated voltage	231 V AC (rms)	Thermal time constant	40 min
Rated power	624 W	Rotor inertia	1.2 kgcm ²
Rated speed	4000 rpm	Protection	IP64
Rated torque	1.49 Nm	Color	RAL 9005
Rated current	1.88 A (rms)	Cooling	Convection
Peak torque	11.4 Nm	Motor-only mass	2.8 kg
Peak current	13.2 A (rms)	Max. axial force 20kh	64 N
Stall torque	3 Nm	Max. radial force 20kh	338 N*
Stall current	3.07 A (rms)	Max. axial force 100kh	38 N
No load speed	6420 rpm	Max. radial force 100kh	198 N*
EMF constant ±10%	59 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.976 Nm / A (rms)		
Torque constant ±10% @ rated load	0.793 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EDM35 (HDSL) multi-turn, 20+12 bits	
Number of poles	10		
Electrical time constant	1.63 ms		
Winding terminal resistance	4.953 Ω		
Rotary field terminal inductance	8.06 mH		
Customs info			
HS Code	85015100		


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

