


Engineering data (WIN 1343)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	2.62 ms
Rated voltage	199 V AC (rms)	Thermal time constant	20 min
Rated power	327 W	Rotor inertia	0.33 kgcm ²
Rated speed	6000 rpm	Protection	IP64
Rated torque	0.52 Nm	Color	RAL 9005
Rated current	1.19 A (rms)	Cooling	Convection
Peak torque	2.47 Nm	Motor-only mass	1.3 kg
Peak current	5.9 A (rms)	Max. axial force 20kh	37 N
Stall torque	0.75 Nm	Max. radial force 20kh	195 N*
Stall current	1.44 A (rms)	Max. axial force 100kh	22 N
No load speed	12000 rpm	Max. radial force 100kh	114 N*
EMF constant ±10%	31.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.521 Nm / A (rms)		
Torque constant ±10% @ rated load	0.437 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EKM36 (HDSL) multi-turn, 18+12 bits, SIL2	
Number of poles	10		
Electrical time constant	1.13 ms		
Winding terminal resistance	12.438 Ω		
Rotary field terminal inductance	14.1 mH		
Customs info			
HS Code	85015100		


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

