

Engineering data (WIN 1270)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	276 V AC (rms)
Rated power	490 W
Rated speed	6000 rpm
Rated torque	0.78 Nm
Rated current	1.27 A (rms)
Peak torque	4.94 Nm
Peak current	8.33 A (rms)
Stall torque	1.3 Nm
Stall current	1.77 A (rms)
No load speed	8140 rpm
EMF constant ±10%	44.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.734 Nm / A (rms)
Torque constant ±10% @ rated load	0.614 Nm / A (rms)
Number of poles	10
Electrical time constant	1.44 ms
Winding terminal resistance	9.598 Ω
Rotary field terminal inductance	13.8 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.53 ms
Thermal time constant	24 min
Rotor inertia	0.5 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.6 kg
Max. axial force 20kh	43 N
Max. radial force 20kh	225 N*
Max. axial force 100kh	25 N
Max. radial force 100kh	131 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EES37 (HDSL) single-turn, 17 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

