


Engineering data (WIN 1579)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	1.20 ms
Rated voltage	177 V AC (rms)	Thermal time constant	32 min
Rated power	471 W	Rotor inertia	0.85 kgcm ²
Rated speed	6000 rpm	Protection	IP64
Rated torque	0.75 Nm	Color	RAL 9005
Rated current	1.9 A (rms)	Cooling	Convection
Peak torque	8.36 Nm	Motor-only mass	2.2 kg
Peak current	18.8 A (rms)	Max. axial force 20kh	49 N
Stall torque	2.2 Nm	Max. radial force 20kh	260 N*
Stall current	4.29 A (rms)	Max. axial force 100kh	29 N
No load speed	7070 rpm	Max. radial force 100kh	152 N*
EMF constant ±10%	31 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.513 Nm / A (rms)		
Torque constant ±10% @ rated load	0.395 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EES37 (HDSL) single-turn, 17 bits	
Number of poles	10		
Electrical time constant	1.58 ms		
Winding terminal resistance	2.151 Ω		
Rotary field terminal inductance	3.39 mH		
Customs info			
HS Code	85015100		


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

