


Engineering data (WIN 1600)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.21 ms
Rated voltage	280 V AC (rms)	Thermal time constant	32 min
Rated power	580 W	Rotor inertia	0.85 kgcm ²
Rated speed	4500 rpm	Protection	IP64
Rated torque	1.23 Nm	Color	RAL 9005
Rated current	1.43 A (rms)	Cooling	Convection
Peak torque	8.36 Nm	Motor-only mass	2.2 kg
Peak current	9.2 A (rms)	Max. axial force 20kh	54 N
Stall torque	2.2 Nm	Max. radial force 20kh	286 N*
Stall current	2.11 A (rms)	Max. axial force 100kh	32 N
No load speed	6010 rpm	Max. radial force 100kh	167 N*
EMF constant ±10%	63 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.042 Nm / A (rms)		
Torque constant ±10% @ rated load	0.860 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EES37 (HDSL) single-turn, 17 bits	
Number of poles	10		
Electrical time constant	1.58 ms		
Winding terminal resistance	8.941 Ω		
Rotary field terminal inductance	14.1 mH		
Customs info			
HS Code	85015100		


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

