

Engineering data (WIN 710)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	162 V AC (rms)
Rated power	1.9 kW
Rated speed	3000 rpm
Rated torque	6.10 Nm
Rated current	8.77 A (rms)
Peak torque	22.5 Nm
Peak current	40.7 A (rms)
Stall torque	7.5 Nm
Stall current	8.9 A (rms)
No load speed	4300 rpm
EMF constant ±10%	51 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.84 Nm / A (rms)
Torque constant ±10% @ rated load	0.70 Nm / A (rms)
Number of poles	10
Electrical time constant	6.32 ms
Winding terminal resistance	0.76 Ω
Rotary field terminal inductance	4.8 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 5)

Max mechanical speed	9000 rpm
Mech. time constant	0.60 ms
Thermal time constant	30 min
Rotor inertia	3.26 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	5.1 kg
Max. axial force 20kh	124 N
Max. radial force 20kh	653 N*
Max. axial force 100kh	73 N
Max. radial force 100kh	382 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

