


Engineering data (WIN 993)		Mechanical data (setting 5)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.66 ms
Rated voltage	284 V AC (rms)	Thermal time constant	52 min
Rated power	6.6 kW	Rotor inertia	32.7 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	21.00 Nm	Color	RAL 9005
Rated current	16.19 A (rms)	Cooling	Convection
Peak torque	90 Nm	Motor-only mass	18 kg
Peak current	63.9 A (rms)	Max. axial force 20kh	136 N
Stall torque	30 Nm	Max. radial force 20kh	717 N*
Stall current	17.8 A (rms)	Max. axial force 100kh	80 N
No load speed	3720 rpm	Max. radial force 100kh	419 N*
EMF constant ±10%	102 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.69 Nm / A (rms)		
Torque constant ±10% @ rated load	1.30 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback 2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)	
Number of poles	10		
Electrical time constant	14.24 ms		
Winding terminal resistance	0.33 Ω		
Rotary field terminal inductance	4.7 mH		

Customs info	
HS Code	85015220


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

