

Engineering data (WIN 1532)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	231 V AC (rms)
Rated power	624 W
Rated speed	4000 rpm
Rated torque	1.49 Nm
Rated current	1.88 A (rms)
Peak torque	11.4 Nm
Peak current	13.2 A (rms)
Stall torque	3 Nm
Stall current	3.07 A (rms)
No load speed	6420 rpm
EMF constant ±10%	59 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.976 Nm / A (rms)
Torque constant ±10% @ rated load	0.793 Nm / A (rms)
Number of poles	10
Electrical time constant	1.63 ms
Winding terminal resistance	4.953 Ω
Rotary field terminal inductance	8.06 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 5)

Max mechanical speed	12000 rpm
Mech. time constant	1.08 ms
Thermal time constant	40 min
Rotor inertia	1.2 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	2.8 kg
Max. axial force 20kh	61 N
Max. radial force 20kh	324 N*
Max. axial force 100kh	36 N
Max. radial force 100kh	189 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

