| Engineering data (WIN 776) | | |
|---|---|---|
| DC bus voltage | 560 | V DC |
| Nominal AC voltage | 380 | V AC (rms) |
| Rated voltage | 207 | V AC (rms) |
| Rated power | 226 | W |
| Rated speed | 4500 | rpm |
| Rated torque | 0.48 | Nm |
| Rated current | 0.9 | A (rms) |
| Peak torque | 2.16 | Nm |
| Peak current | 4.3 | A (rms) |
| Stall torque | 0.54 | Nm |
| Stall current | 0.93 | A (rms) |
| No load speed | 10710 | rpm |
| EMF constant ±10% | 35 | V AC (rms) / 1000rpm |
| Theoretical torque constant ±10% | 0.58 | Nm / A (rms) |
| Torque constant ±10% @ rated load | 0.53 | Nm / A (rms) |
| Number of poles | 6 | |
| Electrical time constant | 1.25 | ms |
| Winding terminal resistance | 41.1 | Ω |
| Rotary field terminal inductance | 51.2 | mH |

| Customs info | |
|---|---|
| HS Code | 85015100 |


| Mechanical data (setting 5) | | |
|---|---|---|
| Max mechanical speed | 12000 | rpm |
| Mech. time constant | 1.49 | ms |
| Thermal time constant | 12 | min |
| Rotor inertia | 0.07 | kgcm² |
| Protection | IP64 | |
| Color | RAL 9005 | |
| Cooling | Convection | |
| Motor-only mass | 0.93 | kg |
| Max. axial force 20kh | 42 | N |
| Max. radial force 20kh* | 222 | N |
| Max. axial force 100kh | 25 | N |
| Max. radial force 100kh* | 130 | N |

** Defined for point of action at ½ output shaft length*

| Sensors | |
|---|---|
| Temperature | PT1000 {PT1000} |
| Feedback | 2-pole resolver ( ER5Kd411, TS2620N21E11, RE-15-1-A15) |


| Brake | | |
|---|---|---|
| Braking torque | 2.00 | Nm |
| Voltage | 24 | V DC |
| Power @20°C | 11.0 | W |
| Current @20°C | 0.46 | A |
| Inertia | 0.08 | kgcm² |
| Mass | 0.20 | kg |


Torque / speed curve




**EGA101N00000001000**


2x M15, 9 and 12 poles rotary




| Connector 1 (226) | |
|---|---|
| **A** | U |
| **B** | V |
| **C** | W |
| **PE** | PE |
| **1** | Brake+ |
| **2** | Brake- |

| Connector 2 (227) | |
|---|---|
| **2** | Therm+ |
| **3** | S4 |
| **4** | S3 |
| **5** | R2 |
| **6** | Therm- |
| **7** | S2 |
| **8** | S1 |
| **9** | R1 |




| TYP | K1 |
|---|---|
| N2-0028 | 105 |
| N2-0054 | 120 |
| N2-0075 | 135 |
| N2-0095 | 150 |
| N2-0112 | 165 |

| INDEX | ZMĚNA | DATUM | PODPIS |
|---|---|---|---|
| | | | |

| | | | | | |
|---|---|---|---|---|---|
| ZN.MAT. | | T.O. | HMOTNOST kg | MĚŘ. | |
| ROZM.-POLOT. | | | | | |
| POM. ZAŘ. | | | ČSN | TŘ.Č. | |
| VYPR. Ošlejšek | NORM.REF. | | POZN. | Č. KUSOVNÍKU | |
| PŘEKR. Ošlejšek 28.01.22 | | | | | |
| TECHNOL. | SCHVÁLIL Ošlejšek | 19.11.2012 | STARÝ V. | Č.V. | |

NÁZEV

Motor N2

N2057 01 B Z_Y_S1

Listů List