




Engineering data (WIN 795)		Mechanical data (setting 5)	
DC bus voltage	36 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	25 V AC (rms)	Mech. time constant	1.15 ms
Rated voltage	21 V AC (rms)	Thermal time constant	12 min
Rated power	188 W	Rotor inertia	0.09 kgcm ²
Rated speed	2500 rpm	Protection	IP64
Rated torque	0.72 Nm	Color	RAL 9005
Rated current	7.8 A (rms)	Cooling	Convection
Peak torque	2.73 Nm	Motor-only mass	1.5 kg
Peak current	31.2 A (rms)	Max. axial force 20kh	52 N
Stall torque	0.75 Nm	Max. radial force 20kh	276 N*
Stall current	7.7 A (rms)	Max. axial force 100kh	31 N
No load speed	4200 rpm	Max. radial force 100kh	161 N*
EMF constant ±10%	5.9 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.1 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.1 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	6	Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)
Electrical time constant	1.27 ms	Brake	
Winding terminal resistance	0.7 Ω	Braking torque	2.00 Nm
Rotary field terminal inductance	0.89 mH	Voltage	24 V DC
Customs info		Power @20°C	11.0 W
HS Code	85015100	Current @20°C	0.46 A
		Inertia	0.08 kgcm ²
		Mass	0.20 kg



EGA101N00000001000
2x M15, 9 and 12 poles rotary



Connector 1 (226)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-

Connector 2 (227)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

