




Engineering data (WIN 739)		Mechanical data (setting 5)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.73 ms
Rated voltage	193 V AC (rms)	Thermal time constant	27 min
Rated power	942 W	Rotor inertia	1.04 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	3.00 Nm	Color	RAL 9005
Rated current	3.47 A (rms)	Cooling	Convection
Peak torque	10.5 Nm	Motor-only mass	2.9 kg
Peak current	12.3 A (rms)	Max. axial force 20kh	68 N
Stall torque	3.5 Nm	Max. radial force 20kh	356 N*
Stall current	3.41 A (rms)	Max. axial force 100kh	40 N
No load speed	3540 rpm	Max. radial force 100kh	208 N*
EMF constant ±10%	62 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.03 Nm / A (rms)		
Torque constant ±10% @ rated load	0.86 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback 2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)	
Number of poles	10		
Electrical time constant	2.86 ms		
Winding terminal resistance	4.27 Ω		
Rotary field terminal inductance	12.2 mH		
Customs info			
HS Code	85015220		



EGA101N00000001000
 2x M15, 9 and 12 poles rotary



Connector 1 (226)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-

Connector 2 (227)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

