Engineering data (WIN 266)		
DC bus voltage	560	V DC
Nominal AC voltage	330	V AC (rms)
Rated voltage	312	V AC (rms)
Rated power	7.1	kW
Rated speed	2000	rpm
Rated torque	34.00	Nm
Rated current	15.3	A (rms)
Peak torque	120	Nm
Peak current	65	A (rms)
Stall torque	40	Nm
Stall current	16.7	A (rms)
No load speed	2270	rpm
EMF constant ±10%	145	V AC (rms) / 1000rpm
Theoretical torque constant ±10%	2.4	Nm / A (rms)
Torque constant ±10% @ rated load	2.2	Nm / A (rms)
Number of poles	6	
Electrical time constant	23.90	ms
Winding terminal resistance	0.41	Ω
Rotary field terminal inductance	9.8	mH

Customs info	
HS Code	85015220

Mechanical data (setting 5)		
Max mechanical speed	3600	rpm
Mech. time constant	0.94	ms
Thermal time constant	47	min
Rotor inertia	76.1	kgcm²
Protection	IP64	
Color	RAL 9005	
Cooling	Convection	
Motor-only mass	41	kg
Max. axial force 20kh	380	N
Max. radial force 20kh*	2001	N
Max. axial force 100kh	222	N
Max. radial force 100kh*	1170	N

** Defined for point of action at ½ output shaft length*

Sensors	
Temperature	PT1000 {PT1000}
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)

Torque / speed curve



CEA271N00000051000
M40, 8 poles, straight



AEA052N00000201000
M23, 12 poles, straight



Connector 1 (151)	
U	U
V	V
W	W
PE	PE
+	Brake+
-	Brake-
1	Therm+
2	Therm-

Connector 2 (10)	
2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1





TYP	øD	L	K	K1
T8-400	ø38	80	310	378
T8-680	ø38	80	378	446
T8-930	ø42	110	446	514
T8-1150	ø42	110	514	582

INDEX	ZMĚNA	DATUM	PODPIS		
ZN.MAT.			T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.					
POM. ZAŘ.				ČSN	TŘ.Č.
VYPR.	NORM.REF.			POZN.	Č. KUSOVNÍKU
PŘEZK.					
TECHNOL.	SCHVÁLIL		29.5.2006	STARÝ V.	Č.V.
NÁZEV	Motor T8			T8000 00 Z	
				Listů	List