




Engineering data (WIN 757)		Mechanical data (setting 5)							
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm						
Nominal AC voltage	220 V AC (rms)	Mech. time constant	2.78 ms						
Rated voltage	114 V AC (rms)	Thermal time constant	10 min						
Rated power	118 W	Rotor inertia	0.05 kgcm²						
Rated speed	4500 rpm	Protection	IP64						
Rated torque	0.25 Nm	Color	RAL 9005						
Rated current	0.96 A (rms)	Cooling	Convection						
Peak torque	1.12 Nm	Motor-only mass	0.7 kg						
Peak current	4.4 A (rms)	Max. axial force 20kh	36 N						
Stall torque	0.28 Nm	Max. radial force 20kh	189 N*						
Stall current	0.97 A (rms)	Max. axial force 100kh	21 N						
No load speed	12260 rpm	Max. radial force 100kh	110 N*						
EMF constant ±10%	17.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length							
Theoretical torque constant ±10%	0.29 Nm / A (rms)								
Torque constant ±10% @ rated load	0.26 Nm / A (rms)	<table><tr><th colspan="2">Sensors</th></tr><tr><td>Temperature</td><td>PT1000 {PT1000}</td></tr><tr><td>Feedback</td><td>2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)</td></tr></table>		Sensors		Temperature	PT1000 {PT1000}	Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)
Sensors									
Temperature	PT1000 {PT1000}								
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)								
Number of poles	6								
Electrical time constant	1.00 ms								
Winding terminal resistance	26.9 Ω								
Rotary field terminal inductance	26.8 mH								

Customs info	
HS Code	85015100



EGA101N00000001000
 2x M15, 9 and 12 poles rotary



Connector 1 (226)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-

Connector 2 (227)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

