

Engineering data (WIN 807)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	180 V AC (rms)
Rated power	1.2 kW
Rated speed	3000 rpm
Rated torque	3.70 Nm
Rated current	4.46 A (rms)
Peak torque	14.4 Nm
Peak current	17.3 A (rms)
Stall torque	4.8 Nm
Stall current	4.84 A (rms)
No load speed	3660 rpm
EMF constant ±10%	60 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.99 Nm / A (rms)
Torque constant ±10% @ rated load	0.83 Nm / A (rms)
Number of poles	10
Electrical time constant	3.00 ms
Winding terminal resistance	2.5 Ω
Rotary field terminal inductance	7.5 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 16)

Max mechanical speed	12000 rpm
Mech. time constant	0.67 ms
Thermal time constant	30 min
Rotor inertia	1.52 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	3.8 kg
Max. axial force 20kh	75 N
Max. radial force 20kh	392 N*
Max. axial force 100kh	44 N
Max. radial force 100kh	229 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	SRS50 (Hiperface) single-turn, 1024 sin/cos+12bits


BGC110N00001216000

M23, 8 poles, rotary


AGC113N00001215000

M23, 17 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (130)

1/9	SIN/REFSIN
3/11	COS/REFCOS
5/13	DATA/DATA-
4/2	Us/GND
14/7	Therm

