


Engineering data (WIN 1109)		Mechanical data (setting 16)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.02 ms
Rated voltage	334 V AC (rms)	Thermal time constant	80 min
Rated power	5.5 kW	Rotor inertia	49.5 kgcm ²
Rated speed	2000 rpm	Protection	IP64
Rated torque	26.10 Nm	Color	RAL 9005
Rated current	11.72 A (rms)	Cooling	Convection
Peak torque	85 Nm	Motor-only mass	18.5 kg
Peak current	40.8 A (rms)	Max. axial force 20kh	292 N
Stall torque	30 Nm	Max. radial force 20kh	1537 N*
Stall current	11.6 A (rms)	Max. axial force 100kh	171 N
No load speed	2420 rpm	Max. radial force 100kh	899 N*
EMF constant ±10%	157 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	2.6 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	2.2 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	SRS50 (Hiperface) single-turn, 1024 sin/cos+12bits
Electrical time constant	15.88 ms	Brake	
Winding terminal resistance	0.8 Ω	Braking torque	36.00 Nm
Rotary field terminal inductance	12.7 mH	Voltage	24 V DC
Customs info		Power @20°C	26.0 W
HS Code	85015220	Current @20°C	1.08 A
		Inertia	6.20 kgcm ²
		Mass	2.85 kg


BGC110N00001216000

M23, 8 poles, rotary


AGC113N00001215000

M23, 17 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (130)

1/9	SIN/REFSIN
3/11	COS/REFCOS
5/13	DATA/DATA-
4/2	Us/GND
14/7	Therm

