


Engineering data (WIN 777)		Mechanical data (setting 49)	
DC bus voltage	36 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	25 V AC (rms)	Mech. time constant	1.49 ms
Rated voltage	19 V AC (rms)	Thermal time constant	12 min
Rated power	160 W	Rotor inertia	0.07 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	0.51 Nm	Color	RAL 9005
Rated current	7.65 A (rms)	Cooling	Convection
Peak torque	2.08 Nm	Motor-only mass	0.93 kg
Peak current	33.2 A (rms)	Max. axial force 20kh	45 N
Stall torque	0.54 Nm	Max. radial force 20kh	234 N*
Stall current	7.6 A (rms)	Max. axial force 100kh	26 N
No load speed	5710 rpm	Max. radial force 100kh	137 N*
EMF constant ±10%	4.3 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.07 Nm / A (rms)		
Torque constant ±10% @ rated load	0.07 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback SKS36 (Hiperface) single-turn, 128 sin/cos	
Number of poles	6		
Electrical time constant	1.23 ms		
Winding terminal resistance	0.62 Ω		
Rotary field terminal inductance	0.76 mH		
Customs info			
HS Code	85015100		



BGC110N00001216000

M23, 8 poles, rotary



AGC113N00001215000

M23, 17 poles, rotary



Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (130)

1/9	SIN/REFSIN
3/11	COS/REFCOS
5/13	DATA/DATA-
4/2	Us/GND
14/7	Therm

