

**Engineering data (WIN 711)**

|                                   |                            |
|-----------------------------------|----------------------------|
| DC bus voltage                    | 560 V DC                   |
| Nominal AC voltage                | 380 V AC (rms)             |
| Rated voltage                     | 277 V AC (rms)             |
| Rated power                       | 1.9 kW                     |
| Rated speed                       | 3000 rpm                   |
| Rated torque                      | 6.10 Nm                    |
| Rated current                     | 5.14 A (rms)               |
| Peak torque                       | 22.5 Nm                    |
| Peak current                      | 23.8 A (rms)               |
| Stall torque                      | 7.5 Nm                     |
| Stall current                     | 5.2 A (rms)                |
| No load speed                     | 4350 rpm                   |
| EMF constant ±10%                 | 87 V AC (rms)<br>/ 1000rpm |
| Theoretical torque constant ±10%  | 1.44 Nm / A<br>(rms)       |
| Torque constant ±10% @ rated load | 1.19 Nm / A<br>(rms)       |
| Number of poles                   | 10                         |
| Electrical time constant          | 5.90 ms                    |
| Winding terminal resistance       | 2.29 Ω                     |
| Rotary field terminal inductance  | 13.5 mH                    |

**Customs info**

|         |          |
|---------|----------|
| HS Code | 85015220 |
|---------|----------|


**Mechanical data (setting 46)**

|                         |                        |
|-------------------------|------------------------|
| Max mechanical speed    | 9000 rpm               |
| Mech. time constant     | 0.62 ms                |
| Thermal time constant   | 30 min                 |
| Rotor inertia           | 3.26 kgcm <sup>2</sup> |
| Protection              | IP64                   |
| Color                   | RAL 9005               |
| Cooling                 | Convection             |
| Motor-only mass         | 5.1 kg                 |
| Max. axial force 20kh   | 124 N                  |
| Max. radial force 20kh  | 653 N*                 |
| Max. axial force 100kh  | 73 N                   |
| Max. radial force 100kh | 382 N*                 |

\* Defined for point of action at ½ output shaft length

**Sensors**

|             |                                                     |
|-------------|-----------------------------------------------------|
| Temperature | PT1000 {PT1000}                                     |
| Feedback    | SKM36 (Hiperface) multi-turn,<br>128 sin/cos+12bits |


**BGC110N00001216000**

M23, 8 poles, rotary


**AGC113N00001215000**

M23, 17 poles, rotary


**Connector 1 (9)**

|   |        |
|---|--------|
| 1 | U      |
| 4 | V      |
| 3 | W      |
| 2 | PE     |
| A | Brake+ |
| B | Brake- |
| C |        |
| D |        |

**Connector 2 (130)**

|      |            |
|------|------------|
| 1/9  | SIN/REFSIN |
| 3/11 | COS/REFCOS |
| 5/13 | DATA/DATA- |
| 4/2  | Us/GND     |
| 14/7 | Therm      |

