

Engineering data (WIN 933)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	267 V AC (rms)
Rated power	9.4 kW
Rated speed	3000 rpm
Rated torque	30.00 Nm
Rated current	24.35 A (rms)
Peak torque	132 Nm
Peak current	101.6 A (rms)
Stall torque	44 Nm
Stall current	28.3 A (rms)
No load speed	4040 rpm
EMF constant ±10%	94 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.55 Nm / A (rms)
Torque constant ±10% @ rated load	1.23 Nm / A (rms)
Number of poles	10
Electrical time constant	14.74 ms
Winding terminal resistance	0.19 Ω
Rotary field terminal inductance	2.8 mH

Customs info

HS Code	85015230
---------	----------


Mechanical data (setting 46)

Max mechanical speed	6000 rpm
Mech. time constant	0.64 ms
Thermal time constant	62 min
Rotor inertia	47 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	25.9 kg
Max. axial force 20kh	145 N
Max. radial force 20kh	761 N*
Max. axial force 100kh	85 N
Max. radial force 100kh	445 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	SKS36 (Hiperface) single-turn, 128 sin/cos


BGC110N00001216000

M23, 8 poles, rotary


AGC113N00001215000

M23, 17 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (130)

1/9	SIN/REFSIN
3/11	COS/REFCOS
5/13	DATA/DATA-
4/2	Us/GND
14/7	Therm

