



Engineering data (WIN 711)		Mechanical data (setting 29)	
DC bus voltage	560 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.62 ms
Rated voltage	277 V AC (rms)	Thermal time constant	30 min
Rated power	1.9 kW	Rotor inertia	3.26 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	6.10 Nm	Color	RAL 9005
Rated current	5.14 A (rms)	Cooling	Convection
Peak torque	22.5 Nm	Motor-only mass	5.9 kg
Peak current	23.8 A (rms)	Max. axial force 20kh	125 N
Stall torque	7.5 Nm	Max. radial force 20kh	660 N*
Stall current	5.2 A (rms)	Max. axial force 100kh	73 N
No load speed	4350 rpm	Max. radial force 100kh	386 N*
EMF constant ±10%	87 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.44 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	1.19 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EQI1131 (EnDat 2.2) multi-turn, 19 + 12 bits
Electrical time constant	5.90 ms	Brake	
Winding terminal resistance	2.29 Ω	Braking torque	9.00 Nm
Rotary field terminal inductance	13.5 mH	Voltage	24 V DC
Customs info		Power @20°C	18.0 W
HS Code	85015220	Current @20°C	0.75 A
		Inertia	0.60 kgcm ²
		Mass	0.82 kg


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (293)

1	Vcc (+5V)
2	GND
3	DATA
4	DATA-
5	CLOCK
6	CLOCK-
7	Therm+
8	Therm-
9	Vcc sensor
10	GND sensor

