Engineering data (WIN 1613)		
DC bus voltage	560	V DC
Nominal AC voltage	380	V AC (rms)
Rated voltage	191	V AC (rms)
Rated power	555	W
Rated speed	100	rpm
Rated torque	53.00	Nm
Rated current	2.61	A (rms)
Peak torque	163.5	Nm
Peak current	9.4	A (rms)
Stall torque	54.5	Nm
Stall current	2.61	A (rms)
No load speed	300	rpm
EMF constant ±10%	1263	V AC (rms) / 1000rpm
Theoretical torque constant ±10%	20.89	Nm / A (rms)
Torque constant ±10% @ rated load	20.31	Nm / A (rms)
Number of poles	38	
Electrical time constant	3.27	ms
Winding terminal resistance	19.776	Ω
Rotary field terminal inductance	64.6	mH

Customs info	
HS Code	85015100

Mechanical data (setting 6)		
Max mechanical speed	12000	rpm
Mech. time constant	1.26	ms
Thermal time constant	61	min
Rotor inertia	161	kgcm²
Protection	IP00	
Color	RAL 9005	
Cooling	Convection	
Motor-only mass	8.6	kg

Sensors	
Temperature	PT1000 {PT1000}



Connector 1 (259)	
white	U
blue	V
red	W

2x Therm
2x Brake



TYP	A	L
Q5-0280	30	50
Q5-0545	60	80
Q5-0810	90	110
Q5-1070	120	140
Q5-1340	150	170

INDEX	ZMĚNA	DATUM	PODPIS

ZN.MAT.		T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.				
POM. ZAŘ.			ČSN	TŘ.Č.
VYPR. Šimík	NORM.REF.		POZN.	Č. KUSOVNÍKU
PŘEKR.				
TECHNOL.	SCHVÁLIL Ošlejšek	19.10.2016	STARÝ V.	Č.V.

NÁZEV
Motor Q5

Q5000 00 Z

Listů List