


Engineering data (WIN 1614)		Mechanical data (setting 6)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.39 ms
Rated voltage	200 V AC (rms)	Thermal time constant	61 min
Rated power	1.3 kW	Rotor inertia	161 kgcm ²
Rated speed	100 rpm	Protection	IP00
Rated torque	128.70 Nm	Color	RAL 9005
Rated current	5.59 A (rms)	Cooling	Convection
Peak torque	402 Nm	Motor-only mass	19.4 kg
Peak current	20.3 A (rms)	Sensors	
Stall torque	134 Nm	Temperature	PT1000 {PT1000}
Stall current	5.7 A (rms)		
No load speed	260 rpm		
EMF constant ±10%	1432 V AC (rms) / 1000rpm		
Theoretical torque constant ±10%	23.685 Nm / A (rms)		
Torque constant ±10% @ rated load	23.023 Nm / A (rms)		
Number of poles	38		
Electrical time constant	4.20 ms		
Winding terminal resistance	7.903 Ω		
Rotary field terminal inductance	33.2 mH		
Customs info			
HS Code	85015220		



Connector 1 (259)

white U

blue V

red W

2x Therm

2x Brake

