


Engineering data (WIN -504)		Mechanical data (setting 6)	
DC bus voltage	320 V DC	Max mechanical speed	4000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.90 ms
Rated voltage	187 V AC (rms)	Thermal time constant	91 min
Rated power	5.7 kW	Rotor inertia	369 kgcm ²
Rated speed	700 rpm	Protection	IP00
Rated torque	78.10 Nm	Color	RAL 9005
Rated current	19.81 A (rms)	Cooling	Convection
Peak torque	402 Nm	Motor-only mass	19.4 kg
Peak current	113.93 A (rms)	Sensors	
Stall torque	134 Nm	Temperature	PT1000 {PT1000}
Stall current	31.77 A (rms)		
No load speed	860 rpm		
EMF constant ±10%	255 V AC (rms) / 1000rpm		
Theoretical torque constant ±10%	4.22 Nm / A (rms)		
Torque constant ±10% @ rated load	3.94 Nm / A (rms)		
Number of poles	38		
Electrical time constant	4.20 ms		
Winding terminal resistance	0.25 Ω		
Rotary field terminal inductance	1.05 mH		
Customs info			
HS Code	85015220		



Connector 1 (259)

white U

blue V

red W

2x Therm

2x Brake

