

Engineering data (WIN 815)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	166 V AC (rms)
Rated power	226 W
Rated speed	4500 rpm
Rated torque	0.48 Nm
Rated current	1.12 A (rms)
Peak torque	2.16 Nm
Peak current	5.4 A (rms)
Stall torque	0.54 Nm
Stall current	1.17 A (rms)
No load speed	7740 rpm
EMF constant ±10%	28 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.46 Nm / A (rms)
Torque constant ±10% @ rated load	0.43 Nm / A (rms)
Number of poles	6
Electrical time constant	1.27 ms
Winding terminal resistance	25.37 Ω
Rotary field terminal inductance	32.3 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.43 ms
Thermal time constant	12 min
Rotor inertia	0.07 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.15 kg
Max. axial force 20kh	39 N
Max. radial force 20kh	205 N*
Max. axial force 100kh	23 N
Max. radial force 100kh	120 N*

* Defined for point of action at ½ output shaft length


Sensors

Temperature	PT1000 {PT1000}
Feedback	EKS36 (HDSL) single-turn, 17 bits



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

