

Engineering data (WIN 819)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	190 V AC (rms)
Rated power	402 W
Rated speed	6000 rpm
Rated torque	0.64 Nm
Rated current	1.57 A (rms)
Peak torque	3 Nm
Peak current	7.9 A (rms)
Stall torque	0.75 Nm
Stall current	1.71 A (rms)
No load speed	8220 rpm
EMF constant ±10%	26.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.44 Nm / A (rms)
Torque constant ±10% @ rated load	0.41 Nm / A (rms)
Number of poles	6
Electrical time constant	1.35 ms
Winding terminal resistance	13.36 Ω
Rotary field terminal inductance	18 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.08 ms
Thermal time constant	12 min
Rotor inertia	0.09 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.35 kg
Max. axial force 20kh	37 N
Max. radial force 20kh	195 N*
Max. axial force 100kh	22 N
Max. radial force 100kh	114 N*

** Defined for point of action at ½ output shaft length*

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKS36 (HDSL) single-turn, 17 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

