


Engineering data (WIN 1190)		Mechanical data (setting 5)	
DC bus voltage	560 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.78 ms
Rated voltage	241 V AC (rms)	Thermal time constant	25 min
Rated power	2.1 kW	Rotor inertia	2.04 kgcm²
Rated speed	6000 rpm	Protection	IP67
Rated torque	3.40 Nm	Color	RAL 9005
Rated current	7.29 A (rms)	Cooling	Convection
Peak torque	15.3 Nm	Motor-only mass	3.8 kg
Peak current	35.1 A (rms)	Max. axial force 20kh	113 N
Stall torque	5.1 Nm	Max. radial force 20kh	595 N*
Stall current	7.7 A (rms)	Max. axial force 100kh	66 N
No load speed	9460 rpm	Max. radial force 100kh	348 N*
EMF constant ±10%	40 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.66 Nm / A (rms)		
Torque constant ±10% @ rated load	0.47 Nm / A (rms)	Sensors TemperaturePT1000 {PT1000} Feedback2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)	
Number of poles	10		
Electrical time constant	5.46 ms		
Winding terminal resistance	0.97 Ω		
Rotary field terminal inductance	5.3 mH		


Customs info	
HS Code	85015220


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

