

Engineering motordata (WIN 586)

DC bus voltage	48 V DC
Nominal AC voltage	30 V AC (rms)
Rated voltage	22 V AC (rms)
Rated power	113 W
Rated speed	4500 rpm
Rated torque	0.24 Nm
Rated current	4.46 A (rms)
Peak torque	1 Nm
Peak current	18.8 A (rms)
Stall torque	0.26 Nm
Stall current	4.56 A (rms)
No load speed	8590 rpm
EMF constant ±10%	3.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.06 Nm / A (rms)
Torque constant ±10% @ rated load	0.05 Nm / A (rms)
Number of poles	6
Electrical time constant	1.61 ms
Winding terminal resistance	0.88 Ω
Rotary field terminal inductance	1.42 mH

Mechanical motor data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	2.73 ms
Thermal time constant	13 min
Rotor inertia	0.06 kgcm ²
Protection	IP65
Color	RAL 9005
Cooling	Convection

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDM35 (HDSL) multi-turn, 20+12 bits



Brake

Braking torque	0.40 Nm
Voltage	24 V DC
Power @20°C	8.0 W
Current @20°C	0.33 A
Inertia	0.02 kgcm ²
Mass	0.10 kg

Customs info

HS Code	85015100
---------	----------

Gearbox engineering data		Gearbox mechanical data	
Gear ratio	63	Max. radial force	1440 N
Efficiency	95 %*	Max. axial force	1900 N
Torsional stiffness	2.5 Nm/arcmin	Output shaft design	Flange
Rated output torque	18 Nm	Mass	0.47 kg
Max output torque	36 Nm	Input inertia	0.007 kgcm ²
Emergency output torque	90 Nm	Protection	IP64
Rated input speed	2000 rpm	Actuator data	
Max input speed	5000 rpm	Rated speed	32 rpm
Operating temperature	<-25; 50> °C	Rated torque	15.03 Nm
Max. backlash	< 1.5 arcmin	Peak torque	36.00 Nm
Service life	6000 h	Emergency stop torque	63.00 Nm
<i>* at rated speed & torque</i>		EMF constant ±10%	220.5 V AC (rms) / 1000rpm
Lubrication		Torque constant ±10% @ rated load	3.22 Nm / A (rms)
Type	Standard	Output inertia	265.9 kgcm ²
Lubricant	TRIBOL GR TT 1 PD		



Connector 1 (541)

A	Brake+
B	Brake-
C	Motor U
G	PE
J	+Us/DSL+
K	GND/DSL-
L	Motor W
M	Motor V

