

Engineering data (WIN 703)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	248 V AC (rms)
Rated power	355 W
Rated speed	3000 rpm
Rated torque	1.13 Nm
Rated current	1.26 A (rms)
Peak torque	3.45 Nm
Peak current	5 A (rms)
Stall torque	1.15 Nm
Stall current	1.1 A (rms)
No load speed	5980 rpm
EMF constant ±10%	63 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.04 Nm / A (rms)
Torque constant ±10% @ rated load	0.90 Nm / A (rms)
Number of poles	10
Electrical time constant	2.14 ms
Winding terminal resistance	27.76 Ω
Rotary field terminal inductance	59.3 mH

Customs info

HS Code	85015100
---------	----------

Mechanical data (setting 5)


Max mechanical speed	12000 rpm
Mech. time constant	1.37 ms
Thermal time constant	21 min
Rotor inertia	0.31 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection

Sensors

Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)

Brake


Braking torque	4.50 Nm
Voltage	24 V DC
Power @20°C	12.0 W
Current @20°C	0.50 A
Inertia	0.20 kgcm ²
Mass	0.47 kg


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

