

Engineering data (WIN 764)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	278 V AC (rms)
Rated power	2.6 kW
Rated speed	4500 rpm
Rated torque	5.50 Nm
Rated current	6.9 A (rms)
Peak torque	22.5 Nm
Peak current	31.4 A (rms)
Stall torque	7.5 Nm
Stall current	7.3 A (rms)
No load speed	6110 rpm
EMF constant ±10%	62 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.03 Nm / A (rms)
Torque constant ±10% @ rated load	0.80 Nm / A (rms)
Number of poles	10
Electrical time constant	6.17 ms
Winding terminal resistance	1.15 Ω
Rotary field terminal inductance	7.1 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	9000 rpm
Mech. time constant	0.62 ms
Thermal time constant	30 min
Rotor inertia	3.26 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Max. axial force 20kh	108 N
Max. radial force 20kh	571 N*
Max. axial force 100kh	63 N
Max. radial force 100kh	334 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKS36 (HDSL) single-turn, 17 bits



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

