


Engineering data (WIN 787)		Mechanical data (setting 5)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.93 ms
Rated voltage	274 V AC (rms)	Thermal time constant	18 min
Rated power	401 W	Rotor inertia	0.11 kgcm ²
Rated speed	4500 rpm	Protection	IP65
Rated torque	0.85 Nm	Color	RAL 9005
Rated current	1.07 A (rms)	Cooling	Convection
Peak torque	3.8 Nm	Max. axial force 20kh	44 N
Peak current	5.3 A (rms)	Max. radial force 20kh	230 N*
Stall torque	0.95 Nm	Max. axial force 100kh	26 N
Stall current	1.15 A (rms)	Max. radial force 100kh	135 N*
No load speed	7560 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	50 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	0.83 Nm / A (rms)	Temperature	PT1000 {PT1000}
Torque constant ±10% @ rated load	0.79 Nm / A (rms)	Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)
Number of poles	6	Brake	
Electrical time constant	1.44 ms	Braking torque	2.00 Nm
Winding terminal resistance	33.57 Ω	Voltage	24 V DC
Rotary field terminal inductance	48.5 mH	Power @20°C	11.0 W
		Current @20°C	0.46 A
		Inertia	0.08 kgcm ²
		Mass	0.20 kg
Customs info			
HS Code	85015100		




BGC110N00001216000

M23, 8 poles, rotary



AGC052N00001215000

M23, 12 poles, rotary



Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

