




Engineering data (WIN 757)		Mechanical data (setting 5)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	2.78 ms
Rated voltage	114 V AC (rms)	Thermal time constant	10 min
Rated power	118 W	Rotor inertia	0.05 kgcm ²
Rated speed	4500 rpm	Protection	IP64
Rated torque	0.25 Nm	Color	RAL 9005
Rated current	0.96 A (rms)	Cooling	Convection
Peak torque	1.12 Nm	Max. axial force 20kh	41 N
Peak current	4.4 A (rms)	Max. radial force 20kh	216 N*
Stall torque	0.28 Nm	Max. axial force 100kh	24 N
Stall current	0.97 A (rms)	Max. radial force 100kh	126 N*
No load speed	12260 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	17.5 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	0.29 Nm / A (rms)	Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Torque constant ±10% @ rated load	0.26 Nm / A (rms)	Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)
Number of poles	6	Brake	
Electrical time constant	1.00 ms	Braking torque	2.00 Nm
Winding terminal resistance	26.9 Ω	Voltage	24 V DC
Rotary field terminal inductance	26.8 mH	Power @20°C	11.0 W
		Current @20°C	0.46 A
		Inertia	0.08 kgcm ²
		Mass	0.20 kg
Customs info			
HS Code	85015100		



EGA101N00000001000
 2x M15, 9 and 12 poles rotary



Connector 1 (226)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-

Connector 2 (227)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

