



Engineering data (WIN 1056)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.62 ms
Rated voltage	136 V AC (rms)	Thermal time constant	30 min
Rated power	744 W	Rotor inertia	3.26 kgcm ²
Rated speed	1000 rpm	Protection	IP64
Rated torque	7.10 Nm	Color	RAL 9005
Rated current	4.35 A (rms)	Cooling	Convection
Peak torque	22.5 Nm	Max. axial force 20kh	179 N
Peak current	17.5 A (rms)	Max. radial force 20kh	942 N*
Stall torque	7.5 Nm	Max. axial force 100kh	105 N
Stall current	4.09 A (rms)	Max. radial force 100kh	551 N*
No load speed	1970 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	111 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	1.84 Nm / A (rms)	Temperature	PT1000 {PT1000}
Torque constant ±10% @ rated load	1.63 Nm / A (rms)	Feedback	EKS36 (HDSL) single-turn, 17 bits
Number of poles	10		
Electrical time constant	5.92 ms		
Winding terminal resistance	3.68 Ω		
Rotary field terminal inductance	21.8 mH		
Customs info			
HS Code	85015100		



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

