




Engineering data (WIN 783)		Mechanical data (setting 5)	
DC bus voltage	36 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	25 V AC (rms)	Mech. time constant	0.99 ms
Rated voltage	18 V AC (rms)	Thermal time constant	23 min
Rated power	209 W	Rotor inertia	0.55 kgcm ²
Rated speed	1000 rpm	Protection	IP64
Rated torque	2.00 Nm	Color	RAL 9005
Rated current	11.02 A (rms)	Cooling	Convection
Peak torque	6.15 Nm	Max. axial force 20kh	101 N
Peak current	41.9 A (rms)	Max. radial force 20kh	532 N*
Stall torque	2.05 Nm	Max. axial force 100kh	59 N
Stall current	10.3 A (rms)	Max. radial force 100kh	311 N*
No load speed	2060 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	12 V AC (rms) / 1000rpm		
Theoretical torque constant ±10%	0.2 Nm / A (rms)		
Torque constant ±10% @ rated load	0.2 Nm / A (rms)		
Number of poles	10		
Electrical time constant	2.44 ms		
Winding terminal resistance	0.41 Ω		
Rotary field terminal inductance	1 mH		

Customs info	
HS Code	85015100

Sensors	
Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)



EGA101N00000001000
 2x M15, 9 and 12 poles rotary



Connector 1 (226)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-

Connector 2 (227)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

