Engineering data (WIN 950)		
DC bus voltage	560	V DC
Nominal AC voltage	380	V AC (rms)
Rated voltage	309	V AC (rms)
Rated power	1.6	kW
Rated speed	1500	rpm
Rated torque	10.20	Nm
Rated current	3.78	A (rms)
Peak torque	33.9	Nm
Peak current	13.5	A (rms)
Stall torque	11.3	Nm
Stall current	3.63	A (rms)
No load speed	2010	rpm
EMF constant ±10%	188	V AC (rms) / 1000rpm
Theoretical torque constant ±10%	3.11	Nm / A (rms)
Torque constant ±10% @ rated load	2.70	Nm / A (rms)
Number of poles	10	
Electrical time constant	6.32	ms
Winding terminal resistance	5.95	Ω
Rotary field terminal inductance	37.6	mH


Customs info	
HS Code	85015220

Mechanical data (setting 5)		
Max mechanical speed	9000	rpm
Mech. time constant	0.61	ms
Thermal time constant	40	min
Rotor inertia	5.7	kgcm²
Protection	IP64	
Color	RAL 9005	
Cooling	Convection	
Max. axial force 20kh	171	N
Max. radial force 20kh*	898	N
Max. axial force 100kh	100	N
Max. radial force 100kh*	525	N


** Defined for point of action at ½ output shaft length*

Sensors	
Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)


Torque / speed curve



BGC110N00001216000
M23, 8 poles, rotary





AGC052N00001215000
M23, 12 poles, rotary



Connector 1 (9)	
1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)	
2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1





TYP	K
N4-0340	98
N4-0510	113
N4-0750	143
N4-0960	173
N4-1130	203

INDEX	ZMĚNA	DATUM	PODPIS		
ZN.MAT.			T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.					
POM. ZAŘ.				ČSN	TŘ.Č.
VYPR. Ošlejšek		NORM.REF.		POZN.	Č. KUSOVNÍKU
PŘEKR. Ošlejšek 11.07.2021					
TECHNOL.		SCHVÁLIL Ošlejšek	28.01.2021	STARÝ V.	Č.V.
NÁZEV: Motor N4				N4083 00 Z_S4_S1	
				Listů	List