

Engineering data (WIN 955)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	305 V AC (rms)
Rated power	2.1 kW
Rated speed	6000 rpm
Rated torque	3.40 Nm
Rated current	5.72 A (rms)
Peak torque	15.3 Nm
Peak current	27.5 A (rms)
Stall torque	5.1 Nm
Stall current	6 A (rms)
No load speed	7410 rpm
EMF constant ±10%	51 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.84 Nm / A (rms)
Torque constant ±10% @ rated load	0.59 Nm / A (rms)
Number of poles	10
Electrical time constant	5.38 ms
Winding terminal resistance	1.56 Ω
Rotary field terminal inductance	8.4 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	9000 rpm
Mech. time constant	0.77 ms
Thermal time constant	25 min
Rotor inertia	2.04 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Max. axial force 20kh	90 N
Max. radial force 20kh	472 N*
Max. axial force 100kh	52 N
Max. radial force 100kh	276 N*

** Defined for point of action at ½ output shaft length*

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKS36 (HDSL) single-turn, 17 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

