




Engineering data (WIN 707)		Mechanical data (setting 5)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.74 ms
Rated voltage	278 V AC (rms)	Thermal time constant	27 min
Rated power	942 W	Rotor inertia	1.04 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	3.00 Nm	Color	RAL 9005
Rated current	2.42 A (rms)	Cooling	Convection
Peak torque	10.5 Nm	Max. axial force 20kh	75 N
Peak current	10.9 A (rms)	Max. radial force 20kh	394 N*
Stall torque	3.5 Nm	Max. axial force 100kh	44 N
Stall current	2.38 A (rms)	Max. radial force 100kh	231 N*
No load speed	4260 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	89 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	1.47 Nm / A (rms)	Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Torque constant ±10% @ rated load	1.24 Nm / A (rms)	Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)
Number of poles	10	Brake	
Electrical time constant	2.87 ms	Braking torque	4.50 Nm
Winding terminal resistance	8.89 Ω	Voltage	24 V DC
Rotary field terminal inductance	25.5 mH	Power @20°C	12.0 W
Customs info		Current @20°C	0.50 A
HS Code	85015220	Inertia	0.20 kgcm ²
		Mass	0.47 kg



EGA101N00000001000
 2x M15, 9 and 12 poles rotary



Connector 1 (226)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-

Connector 2 (227)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

