


Engineering data (WIN 757)		Mechanical data (setting 49)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	2.78 ms
Rated voltage	114 V AC (rms)	Thermal time constant	10 min
Rated power	118 W	Rotor inertia	0.05 kgcm ²
Rated speed	4500 rpm	Protection	IP64
Rated torque	0.25 Nm	Color	RAL 9005
Rated current	0.96 A (rms)	Cooling	Convection
Peak torque	1.12 Nm	Max. axial force 20kh	36 N
Peak current	4.4 A (rms)	Max. radial force 20kh	189 N*
Stall torque	0.28 Nm	Max. axial force 100kh	21 N
Stall current	0.97 A (rms)	Max. radial force 100kh	110 N*
No load speed	12260 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	17.5 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	0.29 Nm / A (rms)	Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Torque constant ±10% @ rated load	0.26 Nm / A (rms)	Feedback	SKM36 (Hiperface) multi-turn, 128 sin/cos+12bits
Number of poles	6		
Electrical time constant	1.00 ms		
Winding terminal resistance	26.9 Ω		
Rotary field terminal inductance	26.8 mH		
Customs info			
HS Code	85015100		


BGC110N00001216000

M23, 8 poles, rotary


AGC113N00001215000

M23, 17 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (130)

1/9	SIN/REFSIN
3/11	COS/REFCOS
5/13	DATA/DATA-
4/2	Us/GND
14/7	Therm

