


Engineering data (WIN 834)		Mechanical data (setting 5)	
DC bus voltage	560 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.68 ms
Rated voltage	306 V AC (rms)	Thermal time constant	55 min
Rated power	3.1 kW	Rotor inertia	11.5 kgcm ²
Rated speed	2000 rpm	Protection	IP64
Rated torque	14.60 Nm	Color	RAL 9005
Rated current	6.83 A (rms)	Cooling	Convection
Peak torque	48 Nm	Max. axial force 20kh	155 N
Peak current	24 A (rms)	Max. radial force 20kh	817 N*
Stall torque	16 Nm	Max. axial force 100kh	91 N
Stall current	6.8 A (rms)	Max. radial force 100kh	478 N*
No load speed	2670 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	142 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	2.35 Nm / A (rms)	Temperature	PTC 111-K13 {PTC 111-K13 Reissmann}
Torque constant ±10% @ rated load	2.14 Nm / A (rms)	Feedback	2-pole resolver (ER5Kd411, TS2620N21E11, RE-15-1-A15)
Number of poles	10		
Electrical time constant	8.82 ms		
Winding terminal resistance	1.87 Ω		
Rotary field terminal inductance	16.5 mH		
Customs info			
HS Code	85015220		


BGC110N00001216000

M23, 8 poles, rotary


AGC052N00001215000

M23, 12 poles, rotary


Connector 1 (9)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	
D	

Connector 2 (10)

2	Therm+
3	S4
4	S3
5	R2
6	Therm-
7	S2
8	S1
9	R1

