



Engineering data (WIN 726)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.94 ms
Rated voltage	265 V AC (rms)	Thermal time constant	23 min
Rated power	872 W	Rotor inertia	0.55 kgcm ²
Rated speed	4500 rpm	Protection	IP65
Rated torque	1.85 Nm	Color	RAL 9005
Rated current	2.56 A (rms)	Cooling	Convection
Peak torque	6.15 Nm	Max. axial force 20kh	62 N
Peak current	9.1 A (rms)	Max. radial force 20kh	326 N*
Stall torque	2.05 Nm	Max. axial force 100kh	36 N
Stall current	2.25 A (rms)	Max. radial force 100kh	191 N*
No load speed	6880 rpm	<i>* Defined for point of action at ½ output shaft length</i>	
EMF constant ±10%	55 V AC (rms) / 1000rpm	Sensors	
Theoretical torque constant ±10%	0.91 Nm / A (rms)	Temperature	PT1000 {PT1000}
Torque constant ±10% @ rated load	0.72 Nm / A (rms)	Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits
Number of poles	10	Brake	
Electrical time constant	2.51 ms	Braking torque	4.50 Nm
Winding terminal resistance	8.2 Ω	Voltage	24 V DC
Rotary field terminal inductance	20.6 mH	Power @20°C	12.0 W
		Current @20°C	0.50 A
		Inertia	0.20 kgcm ²
		Mass	0.47 kg
Customs info			
HS Code	85015220		



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

