Engineering data (WIN 1306)		
DC bus voltage	560	V DC
Nominal AC voltage	380	V AC (rms)
Rated voltage	305	V AC (rms)
Rated power	3.0	kW
Rated speed	500	rpm
Rated torque	57.00	Nm
Rated current	6.8	A (rms)
Peak torque	180	Nm
Peak current	22.9	A (rms)
Stall torque	60	Nm
Stall current	6.8	A (rms)
No load speed	710	rpm
EMF constant ±10%	537	V AC (rms) / 1000rpm
Theoretical torque constant ±10%	8.882	Nm / A (rms)
Torque constant ±10% @ rated load	8.382	Nm / A (rms)
Number of poles	10	
Electrical time constant	19.08	ms
Winding terminal resistance	2.877	Ω
Rotary field terminal inductance	54.9	mH

Customs info	
HS Code	85015220


Mechanical data (setting 48)		
Max mechanical speed	6000	rpm
Mech. time constant	0.68	ms
Thermal time constant	108	min
Rotor inertia	107	kgcm²
Protection	IP64	
Color	RAL 9005	
Cooling	Convection	
Motor-only mass	30.5	kg
Max. axial force 20kh	314	N
Max. radial force 20kh*	1652	N
Max. axial force 100kh	184	N
Max. radial force 100kh*	966	N

** Defined for point of action at ½ output shaft length*

Sensors	
Temperature	PT1000 {PT1000}
Feedback	EDS35 (HDSL) single-turn, 24 bits


Brake		
Braking torque	36.00	Nm
Voltage	24	V DC
Power @20°C	26.0	W
Current @20°C	1.08	A
Inertia	6.20	kgcm²
Mass	2.85	kg

Torque / speed curve




BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)	
1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+



TYP	K1
N7-3000	240
N7-4000	270
N7-5000	300
N7-6000	330

INDEX	ZMĚNA	DATUM	PODPIS

ZN.MAT.		T.O.	HMOTNOST kg	MĚŘ.	
ROZM.-POLOT.					
POM. ZAŘ.			ČSN	TŘ.Č.	
VYPR. Ošlejšek	NORM.REF.		POZN.	Č. KUSOVNÍKU	
PŘEKR.					
TECHNOL.	SCHVÁLIL Ošlejšek	24.09.2021	STARÝ V.	Č.V.	

NÁZEV
Motor N7

N7036 09 BP Z_S4_S1

Listů List